


# Distributor, Series NL1-DIL

- G 1/4
- Distributor 2x
- Narrow distributor
- suitable for ATEX



Type	Narrow distributor, Can be assembled into blocks
Parts	Distributor
Mounting orientation	Any
Certificates	suitable for ATEX
Working pressure min./max.	0 ... 16 bar
Ambient temperature min./max.	-10 ... 60 °C
Medium temperature min./max.	-10 ... 60 °C
Medium	Compressed air Neutral gases
Weight	0,09 kg

## Technical data

Part No.	Port	Nominal flow	Nominal flow	Nominal flow
		Qn 1►2	Qn 1►3	Qn 1►5
0821300771	G 1/4	2700 l/min	1300 l/min	1300 l/min

Suitable for use in Ex zones 1, 2, 21, 22., Nominal flow Qn with secondary pressure p2 = 6 bar at Δp = 1 bar

## Technical information


The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .  
Suitable for use in Ex zones 1, 2, 21, 22.  
A change in the flow direction (from air supply on the left to air supply on the right) occurs by rotating installation by 180° about the vertical axis. Please see the operating instructions for further details.

## Technical information

Material	
Housing	Die cast zinc

Dimensions

Dimensions



A1 = input  
A2 = output  
A3 = output  
A5 = output

Dimensions in mm

A1	A2	A3	A5	B	C	D	E	J	T2	T3	W
G 1/4	G 1/4	G 1/8	G 1/8	23	18	20	40	40	6	8	30

# Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR\_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.  
2020-12



## CONSIDER IT SOLVED™