

Compressed air tubing, Series TU1-A-PUR

- suitable for dynamic laying
- Ø 3-12 mm
- Polyether polyurethane
- antistatic
- Max. working pressure at 20 °C 10 bar



Max. working pressure at 20 °C 10 bar
 Ambient temperature min./max. -30 ... 60 °C
 Weight See table below

Technical data

Part No.	external	Wall thickness	Color	Length	Bending radius min.	Weight per meter
	-Ø			Delivery unit	At 20 °C	
R412007792	3 mm	0,55 mm	Black	50 m	9 mm	0,006 kg
1820712089	4 mm	0,75 mm	Black	50 m	9 mm	0,009 kg
1820712091	6 mm	1,05 mm	Black	50 m	15 mm	0,02 kg
1820712092	8 mm	1,15 mm	Black	50 m	28 mm	0,03 kg
1820712093	10 mm	1,25 mm	Black	50 m	35 mm	0,042 kg
R412007705	12 mm	1,5 mm	Black	50 m	50 mm	0,063 kg

price / m

Technical information


External calibrated
 Suitable for dynamic laying
 Highly antistatic version with a surface resistance of 1000 k ohm.
 Excellent hydrolysis characteristics
 Excellent UV resistance
 Resistant to microbes

Technical information

Material	
Material	Polyether polyurethane

Diagrams

Pressure-Temperature-Diagram



D = pressure resistance
T = temperature

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



[Facebook.com/EmersonAutomationSolutions](https://www.facebook.com/EmersonAutomationSolutions)



[LinkedIn.com/company/Emerson-Automation-Solutions](https://www.linkedin.com/company/Emerson-Automation-Solutions)



[Twitter.com/EMR_Automation](https://twitter.com/EMR_Automation)

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™