

3/2-directional valve, Series CD04

- Qn = 900 l/min
- Compressed air connection output G 1/8
- single solenoid
- Pipe connection



Type	Spool valve, positive overlapping
Activation	Mechanical
Switching principle	3/2
Sealing principle	Soft sealing
Nominal flow Qn	900 l/min
Working pressure min./max.	-0,95 ... 10 bar
Ambient temperature min./max.	-20 ... 65 °C
Medium temperature min./max.	-20 ... 65 °C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 ... 1 mg/m³
Weight	See table below

Technical data

Part No.		Actuating element	Version	Compressed air connection type
5634000100		Plunger	NC/NO	Internal thread
5634010100		Roller	NC/NO	Internal thread
5634030100		Hand lever, with detent, without detent	NC/NO	Internal thread
5634040100		Hand lever	NC/NO	Internal thread
5634050100		Rotary lever, with detent	NC/NO	Internal thread
5634060100		Button	NC/NO	Internal thread

Part No.	Compressed air connection Input	Compressed air connection Output	Compressed air connection Exhaust
5634000100	G 1/8	G 1/8	G 1/8
5634010100	G 1/8	G 1/8	G 1/8
5634030100	G 1/8	G 1/8	G 1/8
5634040100	G 1/8	G 1/8	G 1/8
5634050100	G 1/8	G 1/8	G 1/8
5634060100	G 1/8	G 1/8	G 1/8

Part No.	Operating force	Material actuating control	Weight	Fig.
	min.			
5634000100	60 N	Stainless steel	0,23 kg	Fig. 1
5634010100	30 N	Polyoxymethylene	0,29 kg	Fig. 2
5634030100	15 N	Polyoxymethylene	0,32 kg	Fig. 3
5634040100	15 N	-	0,29 kg	Fig. 4
5634050100	15 N	Plastic Stainless steel	0,5 kg	Fig. 5
5634060100	60 N	Polyoxymethylene	0,25 kg	Fig. 6

Nominal flow Qn at 6 bar and $\Delta p = 1$ bar

Technical information


option valve: The input and output compressed air connections can be exchanged.
 The valve can thereby be used in the NC or NO operating mode.

Technical information

Material	
Housing	Die cast zinc Polyamide fiber-glass reinforced
Seals	Acrylonitrile butadiene rubber
Actuating element	Stainless steel Polyoxymethylene Plastic, Stainless steel


Dimensions

Dimensions, Fig. 1



1) Stroke 2) Overstroke 3) Ø 4.5 - 12 mm deep


Dimensions, Fig. 2



1) approach angle of rollers max. 30° 2) stroke 3) overstroke


4) 5634010100: Ø20 (POM) / R412008117: Ø19 (ST)

Dimensions, Fig. 3




Position 0: initial position, position I: with detent, manual return, position II: automatic spring return.

Dimensions, Fig. 4




Dimensions, Fig. 5



Dimensions of basic valve apply to all types of actuation.

Dimensions, Fig. 6



1) Stroke 2) Overstroke 3) Ø 4.5 - 12 mm deep

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://emerson.com/aventics)

Your local contact: [Emerson.com/contactus](https://emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™