




5/2-directional valve, Series CD07

- Qn = 1200 l/min
- Compressed air connection output M14x1,5
- With spring return
- Pipe connection
- suitable for ATEX



Type	Spool valve, positive overlapping
Activation	pneumatically
Sealing principle	Soft sealing
Flow rate value Qn	1200 l/min
Working pressure min./max.	-0,95 ... 10 bar
Control pressure min./max.	See table below
Ambient temperature min./max.	-25 ... 80 °C
Medium temperature min./max.	-25 ... 80 °C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 ... 1 mg/m³
Mounting on manifold strip	P-strip PRS strip
Weight	0,5 kg

Technical data

Part No.		Compressed air connection	Compressed air connection
		Input	Output
5710500000		M14x1,5	M14x1,5
5710509300		M14x1,5	M14x1,5
5710501000		M14x1,5	M14x1,5

Part No.	Compressed air connection	Compressed air connection	Control pressure min./max.
	Exhaust	Pilot control exhaust	
5710500000	M14x1,5	M10x1	3 ... 10 bar
5710509300	M14x1,5	M10x1	3 ... 10 bar
5710501000	M14x1,5	M10x1	2 ... 10 bar

Part No.	
5710500000	-
5710509300	1)
5710501000	-

Nominal flow Qn at 6 bar and Δp = 1 bar

1) Protected against dust

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.


Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in the MediaCentre).

Technical information

Material	
Housing	Die cast zinc
Seals	Acrylonitrile butadiene rubber

Dimensions

Dimensions



1) Part No.: 5710501000

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://emerson.com/aventics)

Your local contact: [Emerson.com/contactus](https://emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™