


# 5/2-directional valve, Series 740

- Qn = 700-950 l/min
- Compressed air connection output Ø 8x1 Ø 10x1
- double air pilot
- Pipe connection
- Can be assembled into blocks
- Manual override with detent
- suitable for ATEX



Type	Diaphragm poppet valve
Activation	pneumatically
Pilot	Internal
Sealing principle	Soft sealing
Blocking principle	Single base plate principle Plate principle
Working pressure min./max.	1,5 ... 10 bar
Ambient temperature min./max.	-15 ... 60 °C
Medium temperature min./max.	-15 ... 60 °C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 ... 5 mg/m³
Mounting on manifold strip	PRS strip
Weight	0,23 kg

## Technical data

Part No.	Compressed air connection	
	Input	Output
5717410000	Ø 8x1	Ø 8x1
5717460000	Ø 10x1	Ø 10x1

Part No.	Compressed air connection	Compressed air connection	Flow
	Exhaust	Pilot control exhaust	Qn
5717410000	M14x1	Ø 8x1	700 l/min
5717460000	M14x1	Ø 8x1	950 l/min

Part No.	Throttle
5717410000	with throttle
5717460000	with throttle

Nominal flow Qn at p1 = 6.3 bar and Δp = 1 bar

## Technical information


The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!  
The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .  
The oil content of compressed air must remain constant during the life cycle.  
Use only the approved oils from AVENTICS. Further information can be found in the “Technical information” document (available in the MediaCentre).

## Technical information

Material	
Housing	Polyoxymethylene
Seals	Acrylonitrile butadiene rubber

## Dimensions

### Dimensions




1) for pipe Ø 8 x 1

2) flow control screw for exhausts 5 (R) and 3 (S)

3) position indicator

## Diagrams

## Pilot pressure range



x: operating pressure (bar) y: control pressure (bar)  
a: maximum control pressure depending on operating pressure  
b: minimum control pressure depending on operating pressure

# Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR\_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.  
2020-12



## CONSIDER IT SOLVED™