


4/2-directional valve, Series 840

- Qn = 200 l/min
- Compressed air connection output Ø 6x1
- Single air pilot
- Single air pilot
- With air spring return
- Pipe connection



Type	Poppet valve
Activation	pneumatically
Sealing principle	Soft sealing
Flow rate value Qn	200 l/min
Working pressure min./max.	2 ... 10 bar
Control pressure min./max.	2 ... 10 bar
Ambient temperature min./max.	-15 ... 60 °C
Medium temperature min./max.	-15 ... 60 °C
Medium	Compressed air
Max. particle size	50 µm
Oil content of compressed air	0 ... 1 mg/m³
Mounting on manifold strip	PRS strip
Weight	0,048 kg

Technical data

Part No.	Compressed air connection	
	Input	Output
5718400000	Ø 6x1	Ø 6x1

Part No.	Compressed air connection	
	Exhaust	Pilot control exhaust
5718400000	Ø 6x1	Ø 6x1

Nominal flow Qn at 6 bar and Δp = 1 bar

Technical information

The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

The oil content of compressed air must remain constant during the life cycle.

Use only the approved oils from AVENTICS. Further information can be found in the “Technical information” document (available in the MediaCentre).

The maximum operating pressure depends on the ambient temperature. The following values are applicable:


- 15 °C ... 60°C: Operating pressure 1.5 bar ... 8 bar possible.
- 15 °C ... 40 °C: Operating pressure 1.5 bar ... 10 bar possible.

Technical information

Material	
Housing	Polyoxymethylene
Seals	Acrylonitrile butadiene rubber
Threaded bushing	Polyoxymethylene

Dimensions


Dimensions



1) mounting space for name plate

Diagrams

Control pressure



Pilot pressure range diagram

x: working pressure (bar)

y: pilot pressure (bar)

a: min. pilot pressure at port 14 (Z) depending on working pressure

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™