












# 5/3-directional valve, Series 581, size 3

- ISO 5599-1
- ISO 3
- 5/3
- closed center
- closed center
- $Q_n = 4100 \text{ l/min}$
- Compressed air connection output Base plate ISO 5599-1
- Electrical connection Plug, Form B, industry
- Manual override with detent



|                                  |                             |
|----------------------------------|-----------------------------|
| Type                             | Spool valve                 |
| Sealing principle                | Soft sealing                |
| Blocking principle               | Single base plate principle |
| Connection type                  | Plate connection            |
| Standards                        | ISO 5599-1, ISO 3           |
| Working pressure min./max.       | See table below             |
| Control pressure min./max.       | 3 ... 10 bar                |
| Ambient temperature min./max.    | -15 ... 50 °C               |
| Medium temperature min./max.     | -15 ... 50 °C               |
| Medium                           | Compressed air              |
| Max. particle size               | 50 µm                       |
| Oil content of compressed air    | 0 ... 5 mg/m <sup>3</sup>   |
| Nominal flow $Q_n$               | 4100 l/min                  |
| Flow conductance C               | 14,1 l/(s*bar)              |
| Protection class with connection | IP65                        |
| Duty cycle                       | 100 %                       |
| Typ. switch-on time              | 23 ms                       |
| Typ. switch-off time             | 64 ms                       |
| Mounting screw                   | with hexagon socket         |
| Mounting screw tightening torque | 10 Nm                       |
| Weight                           | 1,01 kg                     |

## Technical data

| Part No.   |                                                                                     | MO                                                                                  |               | Operational voltage DC |
|------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------|------------------------|
| 5813420500 |    |    | closed center | 12 V                   |
| 5813420200 |    |    | closed center | -                      |
| 5813420100 |    |    | closed center | 24 V                   |
| 5813420600 |    |    | closed center | 48 V                   |
| 5813420300 |    |    | closed center | -                      |
| 5813420400 |    |    | closed center | -                      |
| 5813420000 |    |    | closed center | -                      |
| 5813421500 |    |    | closed center | 12 V                   |
| 5813421200 |    |    | closed center | -                      |
| 5813421100 |    |    | closed center | 24 V                   |
| 5813421600 |    |    | closed center | 48 V                   |
| 5813421300 |    |    | closed center | -                      |
| 5813421400 |    |    | closed center | -                      |
| 5813421000 |    |    | closed center | -                      |
| 5813422500 |   |   | closed center | 12 V                   |
| 5813422200 |   |   | closed center | -                      |
| 5813422100 |  |  | closed center | 24 V                   |
| 5813422600 |  |  | closed center | 48 V                   |
| 5813422300 |  |  | closed center | -                      |
| 5813422400 |  |  | closed center | -                      |
| 5813422000 |  |  | closed center | -                      |
| 5813423500 |  |  | closed center | 12 V                   |
| 5813423200 |  |  | closed center | -                      |
| 5813423100 |  |  | closed center | 24 V                   |
| 5813423600 |  |  | closed center | 48 V                   |
| 5813423300 |  |  | closed center | -                      |
| 5813423400 |  |  | closed center | -                      |
| 5813423000 |  |  | closed center | -                      |

| Part No.   | Operational voltage AC 50 Hz | Operational voltage AC 60 Hz | Voltage tolerance DC |
|------------|------------------------------|------------------------------|----------------------|
| 5813420500 | -                            | -                            | -10% / +10%          |
| 5813420200 | 24 V                         | -                            | -                    |
| 5813420100 | -                            | -                            | -10% / +10%          |
| 5813420600 | -                            | -                            | -10% / +10%          |
| 5813420300 | -                            | 110 V                        | -                    |
| 5813420400 | 230 V                        | -                            | -                    |
| 5813420000 | -                            | -                            | -                    |
| 5813421500 | -                            | -                            | -10% / +10%          |
| 5813421200 | 24 V                         | -                            | -                    |
| 5813421100 | -                            | -                            | -10% / +10%          |
| 5813421600 | -                            | -                            | -10% / +10%          |
| 5813421300 | -                            | 110 V                        | -                    |

| Part No.   | Operational voltage<br>AC 50 Hz | Operational voltage<br>AC 60 Hz | Voltage tolerance<br>DC |
|------------|---------------------------------|---------------------------------|-------------------------|
| 5813421400 | 230 V                           | -                               | -                       |
| 5813421000 | -                               | -                               | -                       |
| 5813422500 | -                               | -                               | -10% / +10%             |
| 5813422200 | 24 V                            | -                               | -                       |
| 5813422100 | -                               | -                               | -10% / +10%             |
| 5813422600 | -                               | -                               | -10% / +10%             |
| 5813422300 | -                               | 110 V                           | -                       |
| 5813422400 | 230 V                           | -                               | -                       |
| 5813422000 | -                               | -                               | -                       |
| 5813423500 | -                               | -                               | -10% / +10%             |
| 5813423200 | 24 V                            | -                               | -                       |
| 5813423100 | -                               | -                               | -10% / +10%             |
| 5813423600 | -                               | -                               | -10% / +10%             |
| 5813423300 | -                               | 110 V                           | -                       |
| 5813423400 | 230 V                           | -                               | -                       |
| 5813423000 | -                               | -                               | -                       |

| Part No.   | Voltage tolerance<br>AC 50 Hz | Voltage tolerance<br>AC 60 Hz | Power consumption<br>DC | Holding power<br>AC 50 Hz |
|------------|-------------------------------|-------------------------------|-------------------------|---------------------------|
| 5813420500 | -                             | -                             | 5 W                     | -                         |
| 5813420200 | -10% / +10%                   | -                             | -                       | 8 VA                      |
| 5813420100 | -                             | -                             | 5 W                     | -                         |
| 5813420600 | -                             | -                             | 5 W                     | -                         |
| 5813420300 | -                             | -10% / +10%                   | -                       | -                         |
| 5813420400 | -10% / +10%                   | -                             | -                       | 8 VA                      |
| 5813420000 | -                             | -                             | -                       | -                         |
| 5813421500 | -                             | -                             | 5 W                     | -                         |
| 5813421200 | -10% / +10%                   | -                             | -                       | 8 VA                      |
| 5813421100 | -                             | -                             | 5 W                     | -                         |
| 5813421600 | -                             | -                             | 5 W                     | -                         |
| 5813421300 | -                             | -10% / +10%                   | -                       | -                         |
| 5813421400 | -10% / +10%                   | -                             | -                       | 8 VA                      |
| 5813421000 | -                             | -                             | -                       | -                         |
| 5813422500 | -                             | -                             | 5 W                     | -                         |
| 5813422200 | -10% / +10%                   | -                             | -                       | 8 VA                      |
| 5813422100 | -                             | -                             | 5 W                     | -                         |
| 5813422600 | -                             | -                             | 5 W                     | -                         |
| 5813422300 | -                             | -10% / +10%                   | -                       | -                         |
| 5813422400 | -10% / +10%                   | -                             | -                       | 8 VA                      |
| 5813422000 | -                             | -                             | -                       | -                         |
| 5813423500 | -                             | -                             | 5 W                     | -                         |
| 5813423200 | -10% / +10%                   | -                             | -                       | 8 VA                      |
| 5813423100 | -                             | -                             | 5 W                     | -                         |
| 5813423600 | -                             | -                             | 5 W                     | -                         |
| 5813423300 | -                             | -10% / +10%                   | -                       | -                         |
| 5813423400 | -10% / +10%                   | -                             | -                       | 8 VA                      |

| Part No.   | Voltage tolerance<br>AC 50 Hz | Voltage tolerance<br>AC 60 Hz | Power consumption<br>DC | Holding power<br>AC 50 Hz |
|------------|-------------------------------|-------------------------------|-------------------------|---------------------------|
| 5813423000 | -                             | -                             | -                       | -                         |

| Part No.   | Holding power<br>AC 60 Hz | Switch-on power<br>AC 50 Hz | Switch-on power<br>AC 60 Hz | Pilot    |
|------------|---------------------------|-----------------------------|-----------------------------|----------|
| 5813420500 | -                         | -                           | -                           | Internal |
| 5813420200 | -                         | 10 VA                       | -                           | Internal |
| 5813420100 | -                         | -                           | -                           | Internal |
| 5813420600 | -                         | -                           | -                           | Internal |
| 5813420300 | 8 VA                      | -                           | 10 VA                       | Internal |
| 5813420400 | -                         | 10 VA                       | -                           | Internal |
| 5813420000 | -                         | -                           | -                           | Internal |
| 5813421500 | -                         | -                           | -                           | Internal |
| 5813421200 | -                         | 10 VA                       | -                           | Internal |
| 5813421100 | -                         | -                           | -                           | Internal |
| 5813421600 | -                         | -                           | -                           | Internal |
| 5813421300 | 8 VA                      | -                           | 10 VA                       | Internal |
| 5813421400 | -                         | 10 VA                       | -                           | Internal |
| 5813421000 | -                         | -                           | -                           | Internal |
| 5813422500 | -                         | -                           | -                           | External |
| 5813422200 | -                         | 10 VA                       | -                           | External |
| 5813422100 | -                         | -                           | -                           | External |
| 5813422600 | -                         | -                           | -                           | External |
| 5813422300 | 8 VA                      | -                           | 10 VA                       | External |
| 5813422400 | -                         | 10 VA                       | -                           | External |
| 5813422000 | -                         | -                           | -                           | External |
| 5813423500 | -                         | -                           | -                           | External |
| 5813423200 | -                         | 10 VA                       | -                           | External |
| 5813423100 | -                         | -                           | -                           | External |
| 5813423600 | -                         | -                           | -                           | External |
| 5813423300 | 8 VA                      | -                           | 10 VA                       | External |
| 5813423400 | -                         | 10 VA                       | -                           | External |
| 5813423000 | -                         | -                           | -                           | External |

| Part No.   | Working pressure min./max. | Electrical connection<br>Pilot valve |
|------------|----------------------------|--------------------------------------|
| 5813420500 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813420200 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813420100 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813420600 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813420300 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813420400 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813420000 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813421500 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813421200 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813421100 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813421600 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813421300 | 3 ... 10 bar               | Plug Form B, industry                |

| Part No.   | Working pressure min./max. | Electrical connection<br>Pilot valve |
|------------|----------------------------|--------------------------------------|
| 5813421400 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813421000 | 3 ... 10 bar               | Plug Form B, industry                |
| 5813422500 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813422200 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813422100 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813422600 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813422300 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813422400 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813422000 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813423500 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813423200 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813423100 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813423600 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813423300 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813423400 | -0,95 ... 10 bar           | Plug Form B, industry                |
| 5813423000 | -0,95 ... 10 bar           | Plug Form B, industry                |

| Part No.   | basic valve with electrical connector | Throttle      |
|------------|---------------------------------------|---------------|
| 5813420500 | -                                     | -             |
| 5813420200 | -                                     | -             |
| 5813420100 | -                                     | -             |
| 5813420600 | -                                     | -             |
| 5813420300 | -                                     | -             |
| 5813420400 | -                                     | -             |
| 5813420000 | Basic valve without coil              | -             |
| 5813421500 | -                                     | with throttle |
| 5813421200 | -                                     | with throttle |
| 5813421100 | -                                     | with throttle |
| 5813421600 | -                                     | with throttle |
| 5813421300 | -                                     | with throttle |
| 5813421400 | -                                     | with throttle |
| 5813421000 | Basic valve without coil              | with throttle |
| 5813422500 | -                                     | -             |
| 5813422200 | -                                     | -             |
| 5813422100 | -                                     | -             |
| 5813422600 | -                                     | -             |
| 5813422300 | -                                     | -             |
| 5813422400 | -                                     | -             |
| 5813422000 | Basic valve without coil              | -             |
| 5813423500 | -                                     | with throttle |
| 5813423200 | -                                     | with throttle |
| 5813423100 | -                                     | with throttle |
| 5813423600 | -                                     | with throttle |
| 5813423300 | -                                     | with throttle |
| 5813423400 | -                                     | with throttle |
| 5813423000 | Basic valve without coil              | with throttle |

Nominal flow Qn at 6 bar and  $\Delta p = 1$  bar, MO = Manual override

## Technical information


The min. control pressure must be adhered to, since otherwise faulty switching and valve failure may result!  
The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .  
The oil content of compressed air must remain constant during the life cycle.  
Use only the approved oils from AVENTICS. Further information can be found in the "Technical information" document (available in the MediaCentre).

## Technical information

| Housing | Aluminum                       |
|---------|--------------------------------|
| Seals   | Acrylonitrile butadiene rubber |

## Dimensions

### Dimensions



The pilot valves can be loosened and turned through 180°.

# Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR\_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2021 Emerson Electric Co. All rights reserved.  
2021-07



## CONSIDER IT SOLVED™