



Sealing ring

- Copper



Working pressure min./max. -0,95 ... 15 bar Ambient temperature min./max. -20 ... 150 °C

Technical data


Part No.	Port G	Delivery unit
8661050000	M5	10 piece
8661180000	G 1/8	10 piece
8661140000	G 1/4	10 piece
8661380000	G 3/8	10 piece
8661120000	G 1/2	10 piece
8661340000	G 3/4	10 piece
8661100000	G 1	10 piece
8661150000	G 1 1/2	10 piece

Technical information

Material	
Material	Copper



Dimensions



Dimensions

Part No.	G	d	D	S
8661050000	M5	5.2	7.4	1
8661180000	G 1/8	10.2	13.4	1
8661140000	G 1/4	14.2	17.9	1.5
8661380000	G 3/8	17.2	20.9	1.5
8661120000	G 1/2	21.2	25.9	1.5
8661340000	G 3/4	27.3	32	2
8661100000	G 1	33.5	39	2
8661150000	G 1 1/2	35	48.5	2



Sealing ring, form A DIN 7603 G = thread size

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: Emerson.com/Aventics

Your local contact: Emerson.com/contactus



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and again.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners.

2020 Emerson Electric Co. All rights reserved.

