

Grease

- For rodless cylinders, piston rod cylinders, and valves



Ambient temperature min./max.

See table below

Weight

See table below

Technical data

Part No.	Type	Silicon	Ambient temperature min./max.	Density	
				at	
8315020734	AGS	silicone-free	-40 ... 100 °C	20 °C	0,85 g/cm ³
8315020724	AGS	silicone-free	-40 ... 100 °C	20 °C	0,85 g/cm ³
8315020764	AGS	silicone-free	-40 ... 100 °C	20 °C	0,85 g/cm ³
8981050000	AGR	contains silicon	-25 ... 100 °C	20 °C	0,89 g/cm ³
R499001048	AGF	silicone-free	-30 ... 100 °C	20 °C	0,9 g/cm ³
R499002843	AGF	silicone-free	-30 ... 100 °C	20 °C	0,9 g/cm ³
R412023904	AGH	silicone-free	-30 ... 150 °C	20 °C	1,95 g/cm ³

Part No.	Kinematic viscosity		Reservoir	Weight	
	at				
8315020734	40 °C	150 cSt	Tube	0,02 kg	1)
8315020724	40 °C	150 cSt	Cartridge	0,4 kg	1)
8315020764	40 °C	150 cSt	Socket	1 kg	1)
8981050000	40 °C	280 cSt	Tube	0,04 kg	2)
R499001048	40 °C	400 cSt	Tube	0,02 kg	3)
R499002843	40 °C	400 cSt	Cartridge	0,4 kg	3)
R412023904	40 °C	200 cSt	Tube	0,02 kg	4)

1) Recommended by AVENTICS for cylinders PRA, PRE, TRB, ITS, CPC, KPZ, TRR, GPC and for valves CD04, CD07, and CD12.

2) Recommended by AVENTICS for RTC series cylinders.

3) Recommended by AVENTICS for CCL-IS and CCL-IC series cylinders.

4) Recommended by AVENTICS for PRA, TRB, and ITS series heat-resistant cylinders.

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™