

Series CMS

- M8x1, M12x1
- B-design
- I/O module, active



Version	I/O module, active
Ambient temperature min./max.	0 ... 50 °C
Operational voltage electronics	24 V DC
Protection class	IP65
Weight	0,47 kg
The delivered product may vary from that in the illustration.	

Technical data

Part No.	I/O module version	I/O connection	I/O connection	Fig.
			Number	
R412003489	Digital inputs	Socket (female), M8, 3-pin	8	Fig. 1
R412000871	Digital inputs	Socket (female), M12, 5-pin, A-coded	4	Fig. 2

Scope of delivery incl. 2 tie rod extensions and seal, Manual: PROFIBUS DP - R499050016, DeviceNet - R499050019, Interbus - R412005743, CANopen - R412005742

Technical information

Max. 6 input or 6 output modules may be used.
 You will find assignment schemes for the product in the operating instructions, or contact the nearest AVENTICS sales office.

Technical information

Material	
Housing	Die-cast aluminum

Dimensions

Fig. 1





Fig. 2



Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://emerson.com/aventics)

Your local contact: [Emerson.com/contactus](https://emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™