


Air preparation unit, 2-part, Series AS2-ACD

- G 1/4 G 3/8
- filter porosity 5 µm
- lockable
- for padlocks
- with pressure gauge
- suitable for ATEX



Type	2-part, Can be assembled into blocks
Parts	Filter pressure regulator, Lubricator
Mounting orientation	vertical
Certificates	suitable for ATEX
Working pressure min./max.	1,5 ... 16 bar
Ambient temperature min./max.	-10 ... 50 °C
Medium temperature min./max.	-10 ... 50 °C
Medium	Compressed air Neutral gases
Regulator type	Diaphragm-type pressure regulator
Regulator function	with relieving air exhaust
Adjustment range min./max.	0,5 ... 8 bar
Pressure supply	single
Filter reservoir volume	28 cm³
Filter element	exchangeable
Lubricator reservoir volume	40 cm³
Type of filling	Manual oil filling Semi-automatic oil filling during operation
Weight	See table below

Technical data

Part No.	Port	filter porosity	Flow	Condensate drain
			Qn	
R412006298	G 1/4	5 µm	1800 l/min	semi-automatic, open without pressure
R412006304	G 1/4	5 µm	1800 l/min	semi-automatic, open without pressure
R412006299	G 1/4	5 µm	1800 l/min	fully automatic, open without pressure
R412006300	G 1/4	5 µm	1800 l/min	fully automatic, closed without pressure
R412006307	G 3/8	5 µm	2000 l/min	semi-automatic, open without pressure
R412006308	G 3/8	5 µm	2000 l/min	fully automatic, open without pressure
R412006309	G 3/8	5 µm	2000 l/min	fully automatic, closed without pressure

Part No.	Pressure gauge	Reservoir	Protective guard	Weight	Fig.
R412006298	with pressure gauge	Polycarbonate	Polyamide	0,633 kg	Fig. 1
R412006304	with pressure gauge	Die cast zinc	-	0,633 kg	Fig. 1
R412006299	with pressure gauge	Polycarbonate	Polyamide	0,676 kg	Fig. 1
R412006300	with pressure gauge	Polycarbonate	Polyamide	0,676 kg	Fig. 1
R412006307	with pressure gauge	Polycarbonate	Polyamide	0,633 kg	Fig. 2
R412006308	with pressure gauge	Polycarbonate	Polyamide	0,676 kg	Fig. 2
R412006309	with pressure gauge	Polycarbonate	Polyamide	0,676 kg	Fig. 2

Nominal flow Qn with secondary pressure p2 = 6 bar at Δp = 1 bar

Suitable for use in Ex zones 1, 2, 21, 22.

Technical information

The pressure dew point must be at least 15 °C under ambient and medium temperature and may not exceed 3 °C .

Note: Polycarbonate reservoirs are susceptible to solvents, supplementary information can be found at "Customer information".

Suitable for use in Ex zones 1, 2, 21, 22.

A change in the flow direction (from air supply on the left to air supply on the right) occurs by rotating installation by 180° about the vertical axis. Please see the operating instructions for further details.


Also suitable for separation of fluid oil or water due to the design.

Max. achievable compressed air class acc. to ISO 8573-1:2010 6 : 7 : -

Technical information

Material	
Housing	Polyamide
Front plate	Acrylonitrile butadiene styrene
Seals	Acrylonitrile butadiene rubber
Threaded bushing	Die cast zinc
Reservoir	Polycarbonate Die cast zinc
Protective guard	Polyamide
Filter insert	Polyethylene

Dimensions in mm, Fig. 2



A1 = input

A2 = output

A3 = pressure gauge connection

A7 = condensate drain

1) Plastic reservoir and protective guard with window

2) Metal reservoir with level indicator

3) Semi-automatic condensate drain


4) Fully automatic condensate drain

5) Port for semi-automatic oil filling


6) Mounting option for padlocks, max. shackle Ø 8

Diagrams

Lubricator activation margin




p_1 = working pressure
 q_n = nominal flow

Flow rate characteristic (p₂: 0,5 - 8 bar)

p₁ = Working pressure
p₂ = Secondary pressure
q_n = Nominal flow

Accessories overview



- 1 = contamination display
- 3 = Double nipple
- 4 = Key for E11 locking
- 5 = mortise lock
- 6 = Transition plate DO30
- 7 = Adapter, Series CON-VP
- 8 = Mounting aid DO16, form C
- 9 = Mounting aid DO16, M12
- 10 = Adapter for external pilot air
- 11 = Adapter pneumatic operation
- 12 = Sealing ring

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™