

# Compressed air tubing, Series TU1-S-PAM

- suitable for dynamic laying
- Ø 6 mm
- Polyamide
- Max. working pressure at 20 °C 13-24 bar



Max. working pressure at 20 °C  
Ambient temperature min./max.  
Weight

See table below  
-40 ... 80 °C  
0,011 kg

## Technical data

Part No.	external	Wall thickness	Color	Length	Bending radius min.
	-Ø			Delivery unit	
1820712101	6 mm	1 mm	Natural	25 m	30 mm
1820712111	6 mm	1 mm	Black	25 m	30 mm
R412007515	6 mm	1 mm	Red	25 m	30 mm
R412007516	6 mm	1 mm	Green	25 m	30 mm
R412009915	6 mm	0,65 mm	Blue	25 m	30 mm
R412009998	6 mm	0,65 mm	Silver gray	25 m	30 mm
R412009916	6 mm	0,65 mm	Blue	50 m	30 mm
R412009932	6 mm	0,65 mm	Black	50 m	30 mm
R412009938	6 mm	0,65 mm	Natural	50 m	30 mm
R412009917	6 mm	0,65 mm	Blue	100 m	30 mm
R412009944	6 mm	0,65 mm	Silver gray	100 m	30 mm
R412007636	6 mm	1 mm	Green	100 m	30 mm
R412009905	6 mm	1 mm	Natural	100 m	30 mm
R412009906	6 mm	1 mm	Black	100 m	30 mm

Part No.	Max. working pressure at 20 °C
1820712101	24 bar
1820712111	24 bar
R412007515	24 bar
R412007516	24 bar
R412009915	13 bar
R412009998	13 bar
R412009916	13 bar
R412009932	13 bar

Part No.	Max. working pressure at 20 °C
R412009938	13 bar
R412009917	13 bar
R412009944	13 bar
R412007636	24 bar
R412009905	24 bar
R412009906	24 bar

price / m

Technical information

- External calibrated  
 Halogen-free  
 Excellent hydrolysis characteristics  
 Suitable for dynamic laying  
 Excellent UV resistance  
 Resistant to microbes

Technical information

Material	
Material	Polyamide

# Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR\_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.  
2020-12



## CONSIDER IT SOLVED™