




## Pressure gauge, Series PG1-SFB

- Back port
- Background color White
- Scale color Black, Grey
- Units bar
- Units psi





Type Bourdon tube pressure gauge

Standardization EN 837-1
Class 2,5
Protection class according to EN 60529 IP54

Ambient temperature min./max. -25 ... 60 °C

Medium Compressed air

Main scale unit (outside) bar

Main scale color (outside) Black

Secondary scale unit (inside) psi

Secondary scale color (inside) Grey

Background color White

Pointer color Black

Weight 0,091 kg

## Technical data

Part No.	Compressed air connection	Nominal diameter	Range of application	Display range	Operating pressure	Scale value	
R412010678	R 1/8	50 mm	0 10	0 12	0 12 bar	0,2	1)
R412010679	R 1/8	50 mm	0 10	0 12	0 12 bar	0,2	2)

- 1) Polycarbonate viewing window
- 2) Safety glass viewing window


## Technical information

Material	
Housing	Stainless steel
Thread	Stainless steel
pointer	Stainless steel



## Dimensions


#### Dimensions, Fig. 1, Polycarbonate viewing window







### Dimensions, Fig. 2, Safety glass viewing window



# Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: Emerson.com/Aventics

Your local contact: Emerson.com/contactus



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR\_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and again.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. 

2020 Emerson Electric Co. All rights reserved.

